

PXI

AEROFLEX 20-SLOT CHASSIS

PXI Chassis and System Controller Interface

AEROFLEX
A passion for performance.



20-slot chassis with system control interface

PXI Chassis Assembly Features

- 20-slot PXI Chassis compliant with PXI Specification Rev. 2.2
- One 3U high system controller slot
- Nineteen 3U high PXI/CompactPCI peripheral slots
- A choice of either MXI-4 or MXI-Express interface for external system control
- Includes 19 inch rack mounting brackets
- Automatic fan speed control
- System monitoring for fan speed, internal voltages and temperature

Introduction

The Aeroflex PXI chassis assembly complete with external controller interface kit and rack mounting is equipped with advanced features and functionality compliant with PXI and CompactPCI specifications.

This chassis offers one 3U high system controller slot and nineteen 3U high peripheral slots. Geared towards capacity, the PXI Chassis assembly is the perfect compliment to Aeroflex 3000 Series PXI modular RF instruments for high volume manufacturing environments.

The chassis is supplied with either a MXI-4 or MXIExpress interface kit to enable high speed external control from a compatible personal computer with a single vacant full height PCI expansion slot or a PCIe expansion slot. Each kit comprises a PXI controller module supplied fitted in slot one of the chassis, a PC plug-in interface card and a 3m interface cable. The MXIexpress interface variant is adaptable to be compatible with PCs with either full or half height PCIe expansion slots. Both the MXI-4 and the MXIExpress interfaces bridge to the PCI backplane of the PXI chassis thus providing a transparent interface from the PC controller to PXI instrument module resources.



High Capacity RF Test System

This Chassis assembly populated with Aeroflex 3000 Series instruments and Aeroflex application software together form a complete and formidable RF test system for research and development or manufacturing. This open architecture platform is scalable and re-configurable simply by module addition or exchange. Applications served by any given hardware configuration are completely software definable.

Applications

The chassis assembly enhances the versatility for applications using Aeroflex 3000 Series modules. With 19 available slots, this chassis assembly provides generous expansion opportunities.

For RF testing this permits 2 complete RF transceiver test channels with full duplex interfaces to be populated comprising any configuration of Aeroflex PXI 3000 Series 3 GHz or 6 GHz modules leading to a significantly smaller test system footprint and a lower cost.

Likewise, it is possible to configure systems that provide up to six RF signal generators or signal analyzers in any combination each with either 3 GHz or 6 GHz frequency range in a single 19 inch wide by 4U high rack mountable chassis.

Highlights

The chassis features an intelligent control board that dynamically monitors and manages the chassis status including the fan speed, system voltages, and internal temperature.

The chassis is equipped with a 1100 W dual AC power supply and a forced-air cooling system provided by a dual fan system located at the rear of the chassis. This cooling configuration, in conjunction with air plenums within the chassis, provides airflow for all module slots per the PXI specification and requires no additional rack space for inlet or outlet air.

SPECIFICATIONS - PXI CHASSIS

POWER SUPPLY

AC INPUT

Input voltage range

100 to 240 VAC

Input voltage frequency

50 to 60 Hz

Input current rating

15 A/115 VAC or 10 A/230 VA

DC OUTPUT

Total DC power output: 1120 W

VDC	Maximum
+5 V	120 A (max)
+12 V	64 A (max)
+3.3 V	80 A (max)
-12 V	6 A (max)

COOLING

Fans

2 x 235 CFM fans with filters

PHYSICAL

Number of PXI slots: 20 (1 system slot, 19 peripheral slots)

Dimensions

447 mm x 178 mm x 406 mm (W x H x D)

17.6" x 7" x 16" (W x H x D)

Weight (Chassis only)

13.6 kg (30 lbs.)

OPERATING ENVIRONMENT

Ambient temperature

0°C to 55°C

STORAGE ENVIRONMENT

Ambient temperature

-20°C to 60°C

GENERAL

Standard warranty

24 months

Safety

IEC 61010-1/EN 61010-1 Safety requirements for electrical equipment for measurement, control, and laboratory use - Part 1: General requirements

ELECTROMAGNETIC COMPATIBILITY

Immunity

EN 61326-1

CE COMPLIANCE

The 20 slot chassis meets the essential requirements of applicable European Directives.

SPECIFICATION - MXI & MXI EXPRESS BOARDS

MXI-4 (NI PXI-PCI8331)

CORE FEATURES - PHYSICAL

Dimensions

PXI card	1-slot 3U PXI module
PCI card	107 x 175 (mm) [4.4 x 6.9 in]

Slot requirements

PXI card	1 system slot
PCI card	1 full height PCI slot

Cable length

3 m

ENVIRONMENT

Operating temperature

0 to 55°C

Storage temperature

-20 to 70°C

Relative humidity

5 to 95%, non-condensing

GENERAL

Standard warranty

24 months

MXI EXPRESS (NI PXI-PCIE8361)

CORE FEATURES - PHYSICAL

Dimensions

PXI card	1-slot 3U PXI module
PCIe card	107 x 175 (mm) [4.4 x 6.9 in]

Slot requirements

PXI card	1 system slot
PCI card	1 full height PCI slot

Cable length

3 m

ENVIRONMENT

Operating temperature

0 to 55°C PXI / 0 to 40°C PCI

Storage temperature

-20 to 70°C

Relative humidity

5 to 95%, non-condensing

GENERAL

Standard warranty

24 months

VERSIONS, OPTIONS AND ACCESSORIES

When ordering please quote the full ordering number information.

All variants of the 20-slot chassis are supplied with:

EMC blanking panels

CDROM

Ordering Numbers

82548

82547

Versions

20 Slot PXI Chassis with MXI express interface and rack mount

20 Slot PXI Chassis with MXI-4 interface and rack mount

CHINA Beijing

Tel: [+86] (10) 6539 1166
Fax: [+86] (10) 6539 1778

CHINA Shanghai

Tel: [+86] (21) 5109 5128
Fax: [+86] (21) 5150 6112

FINLAND

Tel: [+358] (9) 2709 5541
Fax: [+358] (9) 804 2441

FRANCE

Tel: [+33] 1 60 79 96 00
Fax: [+33] 1 60 77 69 22

GERMANY

Tel: [+49] 8131 2926-0
Fax: [+49] 8131 2926-130

HONG KONG

Tel: [+852] 2832 7988
Fax: [+852] 2834 5364

INDIA

Tel: [+91] (0) 80 4115 4501
Fax: [+91] (0) 80 4115 4502

JAPAN

Tel: [+81] 3 3500 5591
Fax: [+81] 3 3500 5592

KOREA

Tel: [+82] (2) 3424 2719
Fax: [+82] (2) 3424 8620

SCANDINAVIA

Tel: [+45] 9614 0045
Fax: [+45] 9614 0047

SPAIN

Tel: [+34] (91) 640 11 34
Fax: [+34] (91) 640 06 40

UK Cambridge

Tel: [+44] (0) 1763 262277
Fax: [+44] (0) 1763 285353

UK Stevenage

Tel: [+44] (0) 1438 742200
Fax: [+44] (0) 1438 727601
Freephone: 0800 282388

USA

Tel: [+1] (316) 522 4981
Fax: [+1] (316) 522 1360
Toll Free: 800 835 2352

As we are always seeking to improve our products, the information in this document gives only a general indication of the product capacity, performance and suitability, none of which shall form part of any contract. We reserve the right to make design changes without notice. All trademarks are acknowledged. Parent company Aeroflex, Inc. ©Aeroflex 2009.

www.aeroflex.com
info-test@eroflex.com



Our passion for performance is defined by three attributes represented by these three icons: solution-minded, performance-driven and customer-focused.